



PHYSICAL SPECIFICATION

Nominal Voltage		12V
Nominal Capacity (20HR)		8AH
Dimensions	Length	151 ± 1mm (5.94 inches)
	Width	65 ± 1mm (2.56 inches)
	Container Height	95 ± 2 mm (3.74 inches)
	Total Height	101 ± 1mm (3.98 inches)
Weight		Approx 2.5 kg (5.5 lbs)
Standard Terminal		F1-Fasten Tab No. 187E

PRB128T(12V8AH)

Major Application(s):
Security System & UPS



ELECTRICAL SPECIFICATION

Capacity	20 hour rate (0.40A)	8.00AH	It is recommended to use constant-voltage charge and recharge immediately after use		
	10 hour rate (0.72A)	7.25AH	Constant-Voltage Charge	Cycle	Initial Charging Current less than 2.4 A Voltage 14.4V~15.0V at 25°C (77°F) Temperature Coefficient -30mV/°C
	5 hour rate (1.34A)	6.68AH			
	1 hour rate (4.80A)	4.80AH		Standby	Voltage 13.5V~13.8V at 25°C (77°F) Temperature Coefficient -20mV/°C
Capacity Affected by Temperature	40°C (104°F) 25°C (77°F) 0°C (32°F)	105% 100% 85%			
Internal Resistance	Fully charged battery (25°C, 77°F) 25mΩ				

