

# CLASS D EXTINGUISHERS



680R



681R

## 150 lb. Regulated Pressure SODIUM CHLORIDE 250 Lb. Regulated Pressure COPPER POWDER

Two choices for large volume Class D (flammable metal) protection. Model 680 (Sodium Chloride) is effective on magnesium, sodium, potassium, and sodium potassium alloy fires. Model 681 (Copper Powder) designed specifically for fighting difficult lithium fires. Well balanced for quick transport on 36" non-sparking rubber tread steel wheels. Both are pressurized with Argon and regulated to a low 125 psi to avoid disrupting the burning materials.

## FEATURES

- Stainless-steel collars
- Chrome-plated brass fill caps
- Brass hose fittings
- Live swivels on discharge valve
- Heavy-duty steel cylinder, carriage, hose rack
- FM label with QR code
- Large instruction pictogram
- DOT/TC argon cylinder with quick-opening brass valve
- Chrome-plated brass regulator
- Extention wand included (nozzle sold separately)
- 6-Year Warranty

### CONFORMS TO TEST STANDARDS:

CAN/ULC-S504 - UL 299 &  
CAN/ULC-S508 - UL 711

SPECIFICATIONS	CLASS D	
MODEL NUMBER	680R	681R
AGENT TYPE	SUPER D (SODIUM CHLORIDE)	COPPER
CAPACITY (LBS. / KG)	150 / 68	250 / 113.33
SHIPPING WT. (LBS. / KG)	444 / 201.28	544 / 246.61
HEIGHT (IN. / CM)	52 / 132.08	
WIDTH (IN. / CM)	28 / 71.12	
DEPTH (IN. / CM)	45 / 114.3	
DISCHARGE TIME (SEC.)	80	120
GAS CYLINDER	DOT 3AA2015	DOT 3AA2015
DISCHARGE RANGE (FT. / M) WITH APPLICATOR	4 - 8 / 1.31 - 2.62	
OPERATING TEMP. (F / C)	-40° TO +120° / -40° TO +49°	
ARGON CYLINDER (CU.FT. / LITER)	110 / 3115	
HOSE LENGTH (FT. / M)	25 / 7.70	
HOSE DIAMETER (IN. / CM)	.75 / 1.90	
WHEELS [STEEL] (IN. / CM) WITH NON-SPARKING RUBBER TREADS	36 X 2.5 / 91.44 X 6.35	
USCG APPROVED	NO	
FM APPROVED	YES	