PURPLE K DRY CHEMICAL

OPTION

USCG approved with bracket

listed on UL label

Chrome cylinders

(see chart below)

RUGGED

- 6-Year manufacturer's warranty
- Stored pressure design
- Dependable drawn-steel cylinders
- Durable high-gloss polyester powder paint
- All-metal valve construction

BRASS VALVE— HEAVY DUTY

- Chrome-plated brass valve body
- Stainless steel handle & lever


ALUMINUM VALVE— LIGHT TO MEDIUM DUTY

- Anodized aluminum valve body
- · Anodized aluminum handle & lever



ALUMINUM VALVE

USER-FRIENDLY PURPLE K extinguishers contain specially fluidized and siliconized potassium bicarbonate dry chemical that Easy and economical to maintain is particularly effective on Class B flammable liquids, and service pressurized gases, and Class C electrical fires. It is QR coded and multilingual labels





BRASS VALVE

MANUFACTURED AND TESTED TO ANSI/UL STANDARDS

COMPLIES WITH NFPA 10 STANDARD ISO-9001/ ISO-14001 CERTIFIED UL LISTED **CONFORMS TO TEST STANDARDS:**

CAN/ULC-S504 - UL 299 & CAN/ULC-S508 - UL 711

AVAILABLE IN WHEELED EXTINGUISHERS



LARGEST SELECTION OF SIZE AND EXTINGUISHER OPTIONS AVAILABLE.

AGENT TYPE	PURPLE K DRY CHEMICAL						
VALVE TYPE	Anodized Aluminum					Chrome-Plated Brass	
DESIGN	Nozzle			Hose & Nozzle			
MODEL NUMBER	376T	377	B410T	B479/B479T	A413	B460	415
UL & ULC RATING	2B:C	10B:C	10B:C	30B:C	120B:C	80B:C	120B:C
CAPACITY (LBS.)	1	2.5	2.5	5	20	10	20
SHIPPING WT. (LBS.)	2.25	5.5	5.5	9.5	36.4	19.5	38
HEIGHT (IN.)	10.25	14.79	15.5	15.25	24	20.5	24
WIDTH (IN.)	3.94	5.5	5.5	7.25	10.25	8.75	10.25
DEPTH (IN.)	2.63	3	3	4.25	7	5	7
RANGE (INITIAL- FT.)	5-8	5-8	9-15	12-18	15-21	15-21	15-21
DISCHARGE TIME (SEC.)	8.5	8.5	9.5	12	28	22	28
OPTIONAL CHROME CYLINDER	Yes		Yes	Yes		Yes	
NOMINAL OPERATING PRESSURE	125 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG	195 PSIG
INCLUDED BRACKET	Vehicle	Wall	Vehicle	Wall/Vehicle	Wall		