

Z-SERIES HIGH PERFORMANCE

Z-Series extinguishers are the ultimate choice in fire extinguishers for high hazard, frequent use, and extreme environment applications. They are economical—less initial cost, lower maintenance costs, and greater reliability than cartridge-operated extinguishers. Amerex Z-Series extinguishers are available with a proprietary, zinc-enriched coating that resists corrosion for up to 12 years in severely salt-contaminated environments.



RUGGED

- 12-Year manufacturer's warranty
- Zinc-enriched coating
- All-metal valve construction
- Chrome-plated brass gauge guards
- Protective rubber foot rings
- Superior vertical and horizontal range
- Higher operating pressure
- Temperature range -65°F to 120°F

AGENTS

- ABC or Purple K

FAST FLOW

790, 791, 792, 793, 794, 795, 796

COMPLIANCE FLOW

713, 714, 715, 716, 717, 718

USER-FRIENDLY

- Wide grip allows clearance for gloved hand
- Large loop stainless steel pull pin
- QR coded and multilingual labels

FAST FLOW

- High flow rate
- Fast discharge
- Quicker knockdown
- More operator protection

COMPLIANCE FLOW

- Long range
- Highest UL ratings

OPTION

- USCG approved with bracket listed on UL label
- Hot dip galvanized USCG brackets available

AVAILABLE IN 125-AND 250-LB. WHEELED EXTINGUISHERS



MANUFACTURED AND TESTED TO UL STANDARDS

COMPLIES WITH NFPA 10 STANDARD
ISO-9001 AND ISO-14001 CERTIFIED UL LISTED

CONFORMS TO TEST STANDARDS:

CAN/ULC-S504 - UL 299 &
CAN/ULC-S508 - UL 711

AFFORDABLE AND EASY TO MAINTAIN

AGENT TYPE	ABC DRY CHEMICAL			PURPLE K DRY CHEMICAL				ABC DRY CHEMICAL			PURPLE K DRY CHEMICAL		
PERFORMANCE	Fast Flow							Compliance Flow					
VALVE TYPE	Chrome-Plated Brass with Gauge Guard												
DESIGN	Hose & Nozzle												
MODEL NUMBER	790	791	792	793	794	795	796	713	714	715	716	717	718
UL & ULC RATING	2A:40B:C	4A:40B:C	4A:40B:C	40B:C	40B:C	20B:C	40B:C	4A:80B:C	10A:120B:C	10A:160B:C	80B:C	120B:C	160B:C
CAPACITY (LBS./KG)	13.2/6	20/9	30/13.6	13.2/6	20/9	20/9	30/13.6	13.2/6	20/9	30/13.6	13.2/6	20/9	30/13.6
SHIPPING WT. (LBS.)	29	40	56	29	40	40	56	29	40	56	29	40	56
HEIGHT (IN.)	17.5	24.75	26.5	17.5	24.75	24.75	26.5	17.5	24.75	26.5	17.5	24.75	26.5
WIDTH (IN.)	10.5	10.5	11	10.5	10.5	10.5	11	10.5	10.5	11	10.5	10.5	11
DEPTH (IN.)	7	7	8	7	7	7	8	7	7	8	7	7	8
RANGE (INITIAL- FT.)	40-50			40-50				40-50			40-50		
DISCHARGE TIME (SEC.)	15	18	21	15	15	10	16	22	30	34	22	29	34
AVERAGE DISCHARGE RATE (LBS./SEC.)	.94	1.20	1.60	.94	1.44	2.00	1.88	.59	.65	.95	.61	.67	.81
NOMINAL OPERATING PRESSURE	240 PSIG	240 PSIG	240 PSIG	240 PSIG	240 PSIG	240 PSIG	240 PSIG	240 PSIG	240 PSIG	240 PSIG	240 PSIG	240 PSIG	240 PSIG
INCLUDED BRACKET	Wall			Wall				Wall			Wall		

