

## RED LINE Portable Extinguishers for Metal Alkyls

### Features

- Rugged, durable, reliable fire protection
- Ergonomically designed for maximum operator performance
- Simple and safe operation
- Maintenance checks can be made on all moving parts
- Field rechargeable
- Models 30 lb and 150 lb available
- Manual and parts list available
- Hand portable has twelve-year limited warranty
- Wheeled unit has six-year limited warranty
- Sold and serviced through our network of independent distributors in every state and most countries throughout the world
- Large fill opening allows for fast and easy recharge

### Applications

These RED LINE extinguishers are designed for the protection of facilities where metal alkyls are used, processed, stored or handled. Once ignited, most of these materials will react violently with water.

MET-L-KYL dry chemical suppressing agent was developed for use on fires involving most trialkyl aluminums. Most of these metal-organic compounds are pyrophoric liquids that ignite on contact with air such as triethylaluminum. MET-L-KYL dry chemical is also effective on small Class B fires. MET-L-KYL dry chemical should not be used on fires in combustible metals such as magnesium, sodium, potassium and sodium-potassium.

### Description - Hand Portable Extinguisher

- The rugged dry chemical shell is a three piece steel assembly consisting of a seamless welded tube with a spun top, a bottom closure and a machined collar.
- Forged, non-slip aluminum handle positions the extinguisher at optimum 45° angle for easy carrying. Handle is spring loaded to prevent movement during vibration.
- Each finished shell assembly is hydrostatically tested at three times the operating pressure (600 psi (41.4 bar)) and is designed to withstand a pressure of no less than six times the normal operating pressure.
- Cartridge receiver is made of cast aluminum with a stainless steel insert to prevent thread wear.



003662, 006501

- Stainless steel puncture pin is sealed with impregnated felt washers which seal against moisture and provide lubrication to the pin.
- Split nameplates are etched aluminum with a varnish coating to provide durability, readability and corrosion resistance.
- Large forged aluminum fill cap with indicator seals the shell, protecting the agent from contamination. A tamper seal may also be attached to the fill cap to prevent tampering with the agent.
- Flat gasket and quad ring on fill cap provide a gas and moisture tight seal.

### Description - Wheeled Extinguisher

- The extinguisher agent tank is manufactured of welded steel construction with two elliptical dished heads and welded circumferential seams.
- The tank is designed and constructed for a working pressure of 250 psi (17.2 bar). The top of the tank is fitted with a 4 in. (102 mm) ID (Inside Diameter) fill opening.
- The nitrogen cylinder is mounted in a vertical position and permits easy access. Volume is 110 ft<sup>3</sup> (3.11 m<sup>3</sup>) for model 150-C.
- Each cylinder is equipped with a conventional hand wheel nitrogen cylinder valve and visual pressure gauge. The valve is UL Listed.
- In addition to the standard surface preparation procedures, the steel parts are primed using a corrosion-resistant primer. The top coat is a super durable polyester powder paint and oven cured.
- The fill cap and nozzle body are black anodized for added corrosion-resistance.

## Technical Specifications

	Hand Portable Extinguisher	Wheeled Extinguishers
<b>Model</b>	MET-L-KYL	MET-L-KYL
<b>Model name</b>	ML-I-30-G	CR-I-ML-150-C
<b>Extinguisher Part No.</b>	418291	417270
<b>Agent Capacity</b>	30 lb (13.6 kg)	150 lb (68.0 kg)
<b>UL/ULC Rating</b>	N/A <sup>1</sup>	N/A <sup>1</sup>
<b>Discharge Time</b>	24.5 s	74 s
<b>Maximum Effective Range</b>	25 ft (7.6 m)	25 ft (7.6 m)
<b>Operating Temperature Range</b>	-65 °F to 120 °F (-54 °C to 49 °C)	-40 °F to 120 °F (-40 °C to 49 °C)
<b>Agent Flow Rate</b>	1.2 lb/s (0.5 kg/s)	2.0 lb/s (1 kg/s)
<b>Charged Weight (with agent)</b>	53 lb (24 kg)	468 lb (212 kg)
<b>Dimensions:</b>		
<b>Height</b>	22.5 in. (572 mm)	52 in. (1321 mm)
<b>Width</b>	11.1 in. (282 mm)	29 in. (737 mm)
<b>Depth</b>	8.0 in. (203 mm)	42 in. (1067 mm)

**ML** - MET-L-KYL

<sup>1</sup> May be used on materials noted on front nameplate.

**Note:** The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.  
ANSUL®, RED LINE, and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.