CLASS K WET CHEMICAL

Badger pioneered the use of wet chemical extinguishing agents and equipment technology for commercial kitchen fire protection four decades ago. Badger's innovative design and approach for a safe and effective way to address the various new Class K code requirements in 1997 has become the industry standard for kitchen hand portable fire extinguishers.

The 6 liter and 2.5 gallon fire extinguisher models are simple to use and extremely effective in handling the difficult types of cooking media fire hazard situations found in today's busy commercial kitchens.

Badger wet chemical hand portable fire extinguisher models are ideally suited to supplement commercial cooking appliance fire suppression systems for addressing tough Class K combustible kitchen cooking media fires.

FEATURES

- Heavy-duty chrome plated brass valves
- Non-metal finger guard and protective nozzle orifice seal
- Soft 360° mist discharge stream prevents splashing
- UL Listed—Meets DOT requirements
- Full stainless steel cylinder, base, handle, lever and pull pin
- Hex valve collar tightening ring for easy recharge
- Easy-to-read two-piece nameplates
- Suitable for use at temperatures as low as -40°F (-40°C)
- Factory-filled WC-100-1 (6 liter model)
- Six-year limited warranty

WC-250-1 shipped empty, with agent. Recharge after purpose.

Agent	Potassium Acetate	
Model	WC-100-1	WC-250-1
P/N	25064	23171
Nominal Capacity	1.59 gal / 6 liter	2.5 gal / 9.46 liter
UL Fire Rating	K	
Cylinder Material	Stainless Steel	
Valve Material	Plated Brass	
Handle/Lever Mat	Stainless Steel	
Recharge Expellant	Nitrogen / Air	
Operating Pressure	100 @ 70°F	
Discharge Range	8-12 ft / 2.4-3.7 m	
Nom Discharge Time	50-55 sec	75-80 sec
Height (in / cm)	19.5 / 49.5	24.5 / 62.2
Width (in / cm)	8.75 / 22.2	
Depth (in / cm)	7 / 17.8	
Shipping Wgt	15 lb / 6.8 kg	19 lb / 8.6 kg
USCG Approval	N/A	
Bracket	UB-20(opt)	
Recharge	AC-100, P/N: 25092	AC-250, P/N: 23173

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection or your local distributor for assistance.





Temp range: -40°F (-40°C) to 120°F (49°C)









 Class K symbol is the only symbol displayed on nameplate to reduce operator confusion



Class K Wet Chemical Kitchen Extinguisher

