

IS-mB1 IS-minialite

The IS-mB1 is a compact beacon with an array of six high output L.E.D's. Approvals include ATEX, IECEx and EAC Ex for Zone 0 applications and FM approval for Class I Division 1 and Class I Zone 0 applications.

The IS-mB1 is suitable for all intrinsically safe signalling applications including fire, security and process control.


Features

- Input overload and reverse current protection
- End of line resistor certified
- Prismatic lens optimises L.E.D effectiveness

Approvals

- ATEX certificate: SIRA 05ATEX2084X
- IECEx certificate: IECEx SIR 06.0045X
- FM approved
- GOST-R certificate: POCC GB.JB05.B03365





Specification

Light source:	Array of 6 high intensity L.E.D's.
L.E.D. colours:	Red, Amber, Blue, Green & Clear
Flash modes:	Double flash at 2Hz and 1Hz
Effective intensity cd:	23cd* – measured ref. to I.E.S.
Voltage:	16-28vdc via Zener barrier or galvanic isolator
Current:	25mA typical when powered from 24v supply via 28v 300 Ohm Zener barrier
Ingress protection:	IP65
Rating:	Continuous
Enclosure material:	UL94V0 & 5VA FR ABS & PC
Enclosure color:	RAL3000 Red
Fixings:	Stainless Steel
Cable entries:	2 x M20 clearance gland knockouts. Custom configurations also available.
MTBF:	294.6 years / 2,580,645 hours – MIL 217
Terminals:	0.5 to 2.5mm ²
Operating temp:	-40° to +60°C [-40 to +140°F]
Storage temp:	-40° to +70°C [-40 to +158°F]
Relative humidity:	90% at 20°C [68°F]
Weight:	0.32Kg / 0.71lbs

Part Codes

ISmB1-R/[y]	
ATEX / IECEx / FM	
II 1G Ex ia IIC T4 Ga (-40°C ≤Ta≤ +60°C)	
IS Class I, Zone 0, AEx ia IIC T4	
IS Class I, Division 1, Groups A, B, C, D	
GOST-R	
0Exia IIC T4 IP65 -40° to +60°C	
[y]: Lens color:	A: Amber
	R: Red
	B: Blue
	G: Green
	C: Clear (white LED)
May be powered from any certified Zener barrier or galvanic isolator whose output parameters do not exceed:	
Uo : 28VDC Io : 660mA Po : 1.2W	



Brooks Equipment • 10926 David Taylor Dr, Suite 300 • Charlotte, NC 28262 • 800.826.3473 (P) • 800.433.9265 (F)

Sales@BrooksEquipment.com • www.BrooksEquipment.com

No liability is accepted for any consequence of the use of this document. The technical specification of this unit is subject to change without notice due to our policy of continual product development. All dimensions are approximate. This unit is sold subject to our standard conditions of sale, a copy of which is available on request.